



VISCOTAQ PE OUTER WRAP

Product description

VISCOTAQ OUTERWRAP PE is a heavy duty protective outerwrap with excellent mechanical strength. The outerwrap is UV and weather resistant and can be applied within -30 degrees F to 160 degrees F. Once applied the operating temperature is -49 degrees F to 185 degrees F. The material will help prevent effects from soil, soil stress, etc..

The PE Outerwrap is available in different thicknesses.



Application Procedure

For use in conjunction with the VISCOWRAP ST or HT. Manuals are available upon request.

- Start wrapping under sufficient tension
- Apply with 50% overlap
- Apply within application temperature
- Can be applied by machine as well

Technical Data

Color:	black
Adhesion to backing:	0.56 kg/cm, 3.125 lbs per inch
Tensile strength:	8.93 kg/cm, 50 lbs/inch
Temperature range:	Application: -34 to 71 °C, -30 to 160 °F In Service: -45 to 85 °C, -49 to 185 °F
Elongation:	400%
UV resistance:	excellent
Thickness Recommendation:	15 mils



North & South America

Amcorr Products & Services
8000 IH 10 WEST #600
San Antonio, TX 78230
United States of America
Phone : +1-210-524.7737
Toll free : 877-586.3710(USA only)
Fax : +1-210-524.7732
E-mail : info@amcorrusa.com
:www.amcorrusa.com

Distributed By;

robert

Lukas Enterprises
A Reliable Resource to Industry

Riverside, IL 60546
708-447-8275 / fax 708-447-6100
www.lukasenterprises.com